

Product data sheet

863 HP S

EAN-No. 4000896237234



With safety locking · Length: 116 mm · $\frac{63}{16}$ 1/4 ·



Application:

Small operating angle (4°) enables use in the tightest of spaces, e.g. engines, machine construction, agricultural vehicles and devices, renewable energy (solar, wind turbines)

- A lot more power than with ratchets of the same dimensions
- Latching function of the shift lever provides protection against unwanted switching
- Increased service life thanks to the use of state-of-the-art lubricants in the ratchet mechanism
- Strict production tolerances prevent dirt from getting in
- HAZET internal quality standards guarantee loading capacity far beyond the standard requirements
- High-quality, easy to clean, corrosion-resistant
- Integrated suspension option in the handle
- VPA tested, static torque according to DIN 3122: 100 Nm (DIN: 62 Nm)
- Quick-release safety lock
- Sockets are securely locked in place
- Attached tools can easily be released by pressing the button with just one hand
- Number of teeth: 90 (Opening angle 4°)
- Locking ball
- HAZET 2-component handle
- Surface: chrome-plated
- DIN 3122, ISO 3315
- Made in Germany
- Output: $\frac{63}{16}$ 1/4
- Dimensions: 116 mm
- For manual operation
- **HiPer – The Original**
- Developed and produced "Made in Germany"
- Static AND dynamic – double precision in perfection
- High permanent load for durability
- Ergonomic **shift lever**

Handle	HAZET 2-component handle
Order Number	863 HP S