

Product data sheet

1979 W-82

EAN-No. 4000896227228



L x W x H: 133 mm x 65 mm x 23 mm ·



Application:

Small design for use in areas with restricted access

- **Wireless charging**
 - Efficient and comfortable charging function due to optimised self-positioning of the lamp on the pad
 - 180° adjustable, 8-step lockable base for adjustment of work area illumination
 - Progressively dimmable – optimal light adjustment
 - Strong rubberised holding magnets on the underside and rear side of the housing
 - 360° movable retaining hook
- **Main light:**
 - Operating time 2 – 10 h
 - Luminous flux 30 – 300 lumen
 - 3-watt COB LED
- **Top light:**
 - Operating time top light: 5 h
 - Luminous flux 100 lumen
 - 1-watt LED
- Charging starts immediately after the light is fitted
- 2-component plastic housing with rubberised surface
- 4-stage battery status and state-of-charge display
- Switching on / off as well as switching between top and main light via main button
- Wireless charging pad 1979WP-1 or 1979WP-2 is needed
- Number of batteries: 1 x 3.7 V 1200 mAh Lithium-ion rechargeable battery
- Power supply: Cable-free charging
- LED technology: COB/SMD
- Luminous flux 100%: 300 lm
- Operating time 100%: 2 h
- Charging time: 1.5 h
- Type of protection (IP): IP65
- Protection rating (IK): IK09
- Dimensions: 133 mm x 65 mm x 23 mm

Product data sheet
1979 W-82 EAN-No. 4000896**227228**



Order Number	1979 W-82
--------------	-----------