# Product data sheet

**4903-3** EAN-No. 4000896**179848** 





- Increased safety thanks to load-free installation
- Universal tensioning jaw · adjustable
- · Can be used for almost any spring strut / shock absorber strut
- · Load-free disassembly/assembly with completely relieved shock absorber

#### Innovative mounting and installation concept

- Swivels in horizontal or vertical working position,

  HAZET recommends ergonomic working height: adjust vertically, operate horizontally
- Damage to shock absorbers and head plates impossible (no overload risk)
- Simple, lockable strut mount

### High safety

- · Consistently reliable mounting of head plates
- Thread damage to piston rod impossible
- Permanent fixation of spring throughout operation

## Secured investment - by using existing components of SYSTEM 4900

- Existing basic units 4900-2A and all tensioning jaws of System 4900 may be used
- Use of future applications is assured

## Allows record keeping by scaling

- If recurring, significant time savings by scaling
- Firm fixation eliminates readjustment at the same spring strut (left/right)

#### 4 steps to success:

- 1. Fix spring strut on clamping disc via gripper and brakes
- 2. Grip spring with universal tensioning jaw
- 3. Operate tensioning device with reversible ratchet, cordless screwdriver or pneumatic air ratchet
- 4. Disassemble shock absorber without load and install new one (afterwards in reverse order)
- · Made in Germany
- Net weight: 18.1 kg

Order Number 4903-3