

Product data sheet

6160-1 CT

EAN-No. 4000896155316



Length: 2455 mm · Torque range min-max: 600 – 1600 Nm · Accuracy: 3 % · $\frac{25}{1}$ r ·



- For the highest torque values

1600 Nm torque wrench

Weight only about 14 kg

- Actuating force only 685 N (70 kg) at 1600 Nm
- Length of ratchet shaft 1316.5 mm, handle 1203 mm
- **Accuracy $\pm 3\%$ of the scale value** (6170-1CT: $\pm 4\%$) (in direction of actuation for right-hand tightening)
For left-hand tightening, use our torque wrenches with insert tool
- For industrial climbers
- Application on wind turbines, dockyards, in the aviation industry and heavy industry, on commercial vehicles etc.
- Dismountable in 2 parts (6170-1CT 3 parts) with release tool
- Bag included for safe storage and for carrying or wearing on your back
- Fast screw tightening also with ratchet shaft alone. For torque tightening always use the complete wrench
- Safety:
 - Haptic (close-gap release)
 - Audible (“click” sound)
- **2-component handle** for improved feel
- Simplified locking for adjusting the torque value
- Viewing window for visual checking of the locking
- 4 coloured coding rings (red, yellow, green, black) for markings in the case of personalisation or special workflows
- With calibration certificate and serial number
- DIN EN ISO 6789-2:2017, DIN 3120, ISO 1174-1
- Made in Germany
- Output: $\frac{25}{1}$ r
- Dimensions: 2455 mm
- Net weight: 14 kg
- For manual operation
- Torque range min-max: 600 – 1600 Nm
- Accuracy: 3 %
- Scale Graduation (Nm): 5 Nm
- Actuating force min.-max. kg: 26.1 – 70.1 kg
- Number of teeth: 32 (Opening angle 11.25°)
- Head Thickness a: 36 mm
- Head Width b: 77 mm
- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

Torque tools in industry

Product data sheet

6160-1 CT

EAN-No. 4000896155316



Order Number

6160-1 CT