Product data sheet 9033 P-8 EAN-No. 4000896190515



Length: 371 mm ·



Application:

For working areas with restricted access, suitable for cutting metal sheet and steel

- Extra flat grinding head only 46 mm
- Especially suitable for application in areas with restricted access, e.g. cutting of exhaust pipe clamps when installed
- · Reduced vibrations
- · Quick adjustment (without tools) of protective cover
- Knob for locking the output (spindle locking) enables easy wheel changing
- Wheel holder Ø 3/8" (10 mm)
- Including 1 cut-off wheel 100 x 0.8 x 9.53 mm
- Screw for fixing the abrasive media: strength class 12.9
- Air connection inlet: inside thread (IG) 12.91 mm (1/4")
- Coupler plug: Nominal size 7.2 (included)
- Hose diameter (recommended): 10 mm
- Working pressure (bar): 6.3
- Sound power level: 100.5 db(A) Lp W
- Vibration acceleration: 3.65 m/s2
- Power in watts: 700 Watt
- Cold insulated handle
- Dimensions: 371 mm
- Net weight: 1.7 kg
- Sound pressure level: 89.5 dB(A) Lp A
- Revolutions per minute: 14000
- Air requirement: 113 l/min (1.9 l/sec)

Handle	Cold insulated handle
Order Number	9033 P-8