Product data sheet
6132-1 CT EAN-No. 4000896**078455**

Length: 1284 mm · Torque range min-max: 162,7 – 813,5 Nm · lbf min-max: 120 – 600 lbf.ft · Accuracy: 3 % · 20 ¾"



- **2-component handle** for improved feel
- Simplified locking for adjusting the torque value
- Viewing window for visual checking of the locking
- 4 coloured coding rings (red, yellow, green, black) for markings in the case of personalisation or special workflows
- **According to US standards**
- Scale graduation in **lbf.ft**
- **Accuracy ± 3 % of the scale value** (in direction of actuation for right-hand tightening)
  For left-hand tightening, use our torque wrenches with insert tool
- Safe:
  – Haptic (close-gap release)
  – Audible ("click" sound)
- Safe and fast adjustment of the desired torque value by turning the handle
- **HiPer fine-tooth reversible ratchet** in 6127-1CT (90 teeth · 4° operating angle)
- Knob for additionally locking the set value
- Secure storage in safe box with inspection window
- With calibration certificate and serial number
- DIN EN ISO 6789-2:2017, DIN 3120, ISO 1174-1
- Made in Germany
- Output: 20 ¾"
- Dimensions: 1284 mm
- Net weight: 6.42 kg
- For manual operation
- Torque range min-max: 162.7 – 813.5 Nm
- lbf min-max: 120 – 600 lbf.ft
- Accuracy: 3 %
- Scale Graduation (lbf.ft): 2 lbf.ft
- Effective torque wrench length min.-max. l1 mm: 1182.70 – 1158.70 Nm
- Actuating force min.-max. kg: 14.0 – 71.6 kg
- Number of teeth: 32 (Opening angle 11.25°)
- Head Thickness a: 28.5 mm
- Head Width b: 64 mm
- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

Order Number	6132-1 CT

HAZET-WERK – Hermann Zerver GmbH & Co. KG · ✉ 10 04 61 · 42804 Remscheid
Güldenwerther Bahnhofstrasse 25 – 29 · 42857 Remscheid · GERMANY