Product data sheet 6132-1 CT EAN-No. 4000896078455



Length: 1284 mm \cdot Torque range min-max: 162.7 – 813.5 Nm \cdot lbf min-max: 120 – 600 lbf.ft \cdot Accuracy: 3 % \cdot 20 \cdot 3% \cdot



- 2-component handle for improved feel
- · Simplified locking for adjusting the torque value
- · Viewing window for visual checking of the locking
- · 4 coloured coding rings (red, yellow, green, black) for markings in the case of personalisation or special workflows
- · According to US standards
- · Scale graduation in Ibf.ft
- Accuracy ± 3 % of the scale value (in direction of actuation for right-hand tightening)
 For left-hand tightening, use our torque wrenches with insert tool
- · Safe:
 - Haptic (close-gap release)
 - Audible ("click" sound)
- Safe and fast adjustment of the desired torque value by turning the handle
- HiPer fine-tooth reversible ratchet in 6127-1CT (90 teeth · 4° operating angle)
- Knob for additionally locking the set value
- Secure storage in safe box with display window
- With calibration certificate and serial number
- DIN EN ISO 6789-2:2017, DIN 3120, ISO 1174-1
- Made in Germany
- Output: 20 ¾
- Dimensions: 1284 mmNet weight: 6.42 kg
- For manual operation
- Torque range min-max: 162.7 813.5 Nm
- lbf min-max: 120 600 lbf.ft
- · Accuracy: 3 %
- Scale Graduation (lbf.ft): 2 lbf.ft
- Effective torque wrench length min.-max. I1 mm: 1182.70 1158.70 Nm
- Actuating force min.-max. kg: 14.0 71.6 kg
- Number of teeth: 32 (Opening angle 11.25°)
- Head Thickness a: 28.5 mm
- Head Width b: 64 mm
- No more turning back: Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

Order Number 6132-1 CT