

Product data sheet

4971-6

EAN-No. 4000896281909



Application:

Pressing back the brake pistons on hydraulic disc brakes on bicycles

- Easy application and safe working
- For 4-piston braking systems
- Working range: 6 – 15 mm
- For e.g. **SHIMANO** · **SRAM** · **TEKTRO** · **TRP**
- Solid design especially for 4-piston braking systems
- Continuously adjustable locking mechanism that can be operated with just one hand
 - Continuously adjustable locking makes it possible to avoid the use of "Bleed Blocks" when venting the brake system at a later stage
 - Simplified · made easy · accelerated reset the brake pistons and vent the brake system
- Toggle lever principle ensures easy resetting of the brake pistons with little effort
- Double dip coating
- **Easy application**
 - Position the pliers between the brake pistons (without brake pads) and press the plier legs together
 - No need to remove the wheel
- **Safe working**
 - Parallel spreading process avoids risk of tilting or damage to the brake pistons, especially in ceramic brake pistons
 - Type of actuation provides users with feedback on the piston's movement

Tip: Open the expansion tank before pushing back the pistons.

Only push the pistons back until they lay flush in the brake calliper.

When the wheel is fitted, ensure that the brake disc is positioned between the plates.

- Made in Germany

Order Number

4971-6