## Product data sheet 5292-3 CT CAL EAN-No. 4000896243235



With DAkkS calibration certificate  $\cdot$  Length: 484 mm  $\cdot$  Torque range min-max: 40 – 200 Nm  $\cdot$  Accuracy: 3 %  $\cdot$ 



- Plug connection for holding insert tools
- Torque wrench with DAkkS calibration certificate
- Accuracy ± 3 % of the scale value (in the direction of actuation)
  Can be used for right-hand and left-hand threads by turning the insert tool
- · Safe:
  - Haptic (close-gap release)
  - Audible ("click" sound)
- Designed for rough workshop use
- Wide range of applications for controlled screw tightening in tyre service, bicycle, passenger car and commercial vehicle applications as well as various applications in trade and industry
- Optimised sealing ring to protect against debris
- Handle with better grip for easier power transmission
- Adjustment aid with detent points for optimised operator guidance ensures safe and fast adjustment of the desired torque value by turning the handle
- Safe locking of the setting values by latching function on the rotary assembly
- Rotary assembly in triangular form prevents uncontrolled rolling
- · Lock symbols indicate the respective locking status
- Can be attached to the cable loop through openings on the locking rotary assembly
- Easy-to-read, high-contrast scale
- Permanent readability due to laser marking on the scale bush
- With calibration certificate and serial number
- · Delivery in sturdy Hexa plastic box
- DIN EN ISO 6789-2:2017
- Made in Germany
- Output: 🖽
- Dimensions: 484 mm
- For manual operation
- Torque range min-max: 40 200 Nm
- Accuracy: 3 %
- Scale Graduation (Nm): 1 Nm
- Effective torque wrench length min.-max. I1 mm: 460.00 437.44 Nm
- Actuating force min.-max. kg: 8.9 46.6 kg
- Inside micrometre of the adjusting tool I2: 38.5 mm
- Head Thickness a: 23 mm
- Head Width b: 30 mm

## Product data sheet 5292-3 CT CAL EAN-No. 4000896243235



• No more turning back: Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

**DAkkS calibration certificate** for the professional user, especially for:

- Aviation industry
- · Automobile industry
- New-energy, wind turbines, offshore wind farms
- Petrochemical industry (oil/gas)

Documented traceability guarantees complete verifiability

Order Number 5292-3 CT CAL