Product data sheet 6290-1 CT CAL EAN-No. 4000896193097



With DAkkS calibration certificate \cdot Length: 306 mm \cdot Torque range min-max: 5 – 60 Nm \cdot Accuracy: 2 % \cdot



- · Torque wrench with DAkkS calibration certificate
- · Plug connection for holding insert tools
- Accuracy ± 2 % of the scale value (in the direction of actuation)
 Can be used for right-hand and left-hand threads by turning the insert tool
- Safe:
 - Haptic (close-gap release)
 - Audible ("click" sound)
- · With calibration certificate and serial number
- Safe and fast adjustment of the desired torque value by turning the handle
- Secure storage in safe box with inspection window
- DIN EN ISO 6789-2:2017
- Made in Germany
- Output: 🖭
- Dimensions: 306 mm
- For manual operation
- Torque range min-max: 5 60 Nm
- Accuracy: 2 %
- Scale Graduation (Nm): 0.5 Nm
- Effective torque wrench length min.-max. I1 mm: 281.52 265.02 Nm
- Actuating force min.-max. kg: 1.8 23.1 kg
- Inside micrometre of the adjusting tool I2: 30 mm
- Head Thickness a: 17 mm
- Head Width b: 22 mm
- No more turning back: Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

DAkkS calibration certificate for the professional user, especially for:

- Aviation industry
- · Automobile industry
- New-energy, wind turbines, offshore wind farms
- Petrochemical industry (oil/gas)

Documented traceability guarantees complete verifiability

Order Number 6290-1 CT CAL