

Product data sheet


6282-1 CT

EAN-No. 4000896080540



Length: 240 mm · Torque range min-max: 4 – 40 Nm · Accuracy: 2 % · 



- Plug connection for holding insert tools
- **Accuracy $\pm 2\%$ of the scale value** (in the direction of actuation)
Can be used for right-hand and left-hand threads by turning the insert tool
- Safe:
 - Haptic (close-gap release)
 - Audible ("click" sound)
- With calibration certificate and serial number
- Especially slim design thanks to spring-loaded puller sleeve for locking the setting values
- Safe and fast adjustment of the desired torque value by turning the handle
- DIN EN ISO 6789-2:2017
- Made in Germany
- Output: 
- Dimensions / length: 240 mm
- Net weight: 0.38 kg
- For manual operation
- Torque range min-max: 4 – 40 Nm
- Accuracy: 2 %
- Scale Graduation (Nm): 0.4 Nm
- Effective torque wrench length min.-max. l1 mm: 219.40 – 205.90 Nm
- Actuating force min.-max. kg: 1.9 – 19.8 kg
- Inside micrometre of the adjusting tool l2: 19.5 mm
- Head Thickness a: 17 mm
- Head Width b: 22 mm

Not according to DIN, as the maximum torque value of the square specified in the standard 6789-1:2017 is exceeded

- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

SYSTEM 6200-1 CT insert torque wrench · 2 – 500 Nm · with insert square · accuracy $\pm 2 / 4\%$

Order Number

6282-1 CT