## Product data sheet 6282-1 CT EAN-No. 4000896080540



Length: 240 mm · Torque range min-max: 4 - 40 Nm · Accuracy: 2 % · □ ·



- Plug connection for holding insert tools
- Accuracy ± 2 % of the scale value (in the direction of actuation)
  Can be used for right-hand and left-hand threads by turning the insert tool
- Safe
  - Haptic (close-gap release)
  - Audible ("click" sound)
- · With calibration certificate and serial number
- Especially slim design thanks to spring-loaded puller sleeve for locking the setting values
- Safe and fast adjustment of the desired torque value by turning the handle
- DIN EN ISO 6789-2:2017
- Made in Germany
- Output: 9x12
- Dimensions: 240 mm
- Net weight: 0.38 kg
- For manual operation
- Torque range min-max: 4-40 Nm
- Accuracy: 2 %
- Scale Graduation (Nm): 0.4 Nm
- Effective torque wrench length min.-max. I1 mm: 219.40 205.90 Nm
- Actuating force min.-max. kg: 1.9 19.8 kg
- Inside micrometre of the adjusting tool I2: 19.5 mm
- Head Thickness a: 17 mm
- Head Width b: 22 mm

Not according to DIN, as the maximum torque value of the square specified in the standard 6789-1:2017 is exceeded

• No more turning back: Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

Order Number 6282-1 CT