

Product data sheet

8816 HP

EAN-No. 4000896235063



Length: 200 mm · 10 % ·



Application:

Small operating angle (4°) enables use in the tightest of spaces, e.g. engines, machine construction, agricultural vehicles and devices, renewable energy (solar, wind turbines)

- A lot more power than with ratchets with the same dimensions
- Locking function of the lever prevents unwanted switching
- Increased service life thanks to the use of state-of-the-art lubricants in the ratchet mechanism
- Strict production tolerances prevent dirt from getting in
- HAZET internal quality standards guarantee loading capacity far beyond the standard requirements
- High-quality, easy to clean, corrosion-resistant
- Integrated suspension option in the handle
- VPA tested, static torque according to DIN 3122: 400 Nm (DIN 202 Nm)
- Number of teeth: 90 (Opening angle 4°)
- Locking ball
- HAZET 2-component handle
- Surface: chrome-plated
- DIN 3122, ISO 3315
- Made in Germany
- Output: 10 %
- Dimensions: 200 mm
- Net weight: 0.26 kg
- For manual operation
- **HiPer – The Original**
- Developed and produced "**Made in Germany**"
- Static AND dynamic – double precision in perfection
- High permanent load for durability
- Ergonomic **shift lever**

Handle

HAZET 2-component handle

Order Number

8816 HP