Product data sheet 6290-1 CT EAN-No. 4000896026043



Length: 306 mm · Torque range min-max: 5 - 60 Nm · Accuracy: 2 % · □ ·



- Plug connection for holding insert tools
- Accuracy ± 2 % of the scale value (in the direction of actuation)
 Can be used for right-hand and left-hand threads by turning the insert tool
- Safe:
 - Haptic (close-gap release)
 - Audible ("click" sound)
- With calibration certificate and serial number
- Safe and fast adjustment of the desired torque value by turning the handle
- Secure storage in safe box with inspection window
- DIN EN ISO 6789-2:2017
- Made in Germany
- Output: 🚾
- Dimensions: 306 mm
- Net weight: 0.46 kg
- For manual operation
- Torque range min-max: 5 60 Nm
- Accuracy: 2 %
- Scale Graduation (Nm): 0.5 Nm
- Effective torque wrench length min.-max. I1 mm: 281.52 265.02 Nm
- Actuating force min.-max. kg: 1.8 23.1 kg
- Inside micrometre of the adjusting tool I2: 30 mm
- Head Thickness a: 17 mm
- Head Width b: 22 mm
- No more turning back: Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

Order Number 6290-1 CT