

Product data sheet


6290-1 CT

EAN-No. 4000896026043



Length: 306 mm · Torque range min-max: 5 – 60 Nm · Accuracy: 2 % · 



- Plug connection for holding insert tools
 - **Accuracy $\pm 2\%$ of the scale value** (in the direction of actuation)
Can be used for right-hand and left-hand threads by turning the insert tool
 - Safe:
 - Haptic (close-gap release)
 - Audible ("click" sound)
 - With calibration certificate and serial number
 - Safe and fast adjustment of the desired torque value by turning the handle
 - Secure storage in safe box with inspection window
 - DIN EN ISO 6789-2:2017
 - Made in Germany
 - Output: 
 - Dimensions: 306 mm
 - Net weight: 0.46 kg
 - For manual operation
 - Torque range min-max: 5 – 60 Nm
 - Accuracy: 2 %
 - Scale Graduation (Nm): 0.5 Nm
 - Effective torque wrench length min.-max. l1 mm: 281.52 – 265.02 Nm
 - Actuating force min.-max. kg: 1.8 – 23.1 kg
 - Inside micrometre of the adjusting tool l2: 30 mm
 - Head Thickness a: 17 mm
 - Head Width b: 22 mm
 - **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required
- SYSTEM 6200-1 CT insert torque wrench · 2 – 500 Nm · with insert square · accuracy $\pm 2/4\%$