

# Product data sheet

## 9022 SR-1

EAN-No. 4000896170593



Length: 280 mm ·  $\frac{1}{2}$ " · Powerful pin clutch mechanism



- High occupational safety thanks to reaction-free striking mechanism
- Low-impact
- High torque values – approx. 30% more than standard products
- Rotation speed – approx. 3 x higher than standard products
- Suitable for manual retightening with torque values > 270 Nm (competing products with only approx. 250 Nm)
- Powerful pin clutch mechanism
- Air connection inlet: inside thread (IG) 12.91 mm (1/4" )
- Coupler plug: Nominal size 7.2 (included)
- Hose diameter (recommended): 10 mm
- Working pressure (bar): 6.3
- Sound power level: 98 db(A) Lp W
- Vibration acceleration: 4.53 m/s<sup>2</sup>
- Forward and reverse: single-stage (right/left)
- Cold insulated handle
- Output:  $\frac{1}{2}$ "
- Dimensions: 280 mm
- Net weight: 1.28 kg
- For impact operation
- Tightening torque maximum [Nm]: 102 Nm
- Sound pressure level: 91 dB(A) Lp A
- Revolutions per minute: 400
- Air requirement: 113 l/min (1.9 l/sec)

<b>Handle</b>	Cold insulated handle
<b>Order Number</b>	9022 SR-1