

Product data sheet

6293-1 CT CAL

EAN-No. 4000896193288



With DAkkS calibration certificate · Length: 625 mm · Torque range min-max: 60 – 320 Nm · Accuracy: 2 % ·

.



- Torque wrench **with DAkkS calibration certificate**
 - Plug connection for holding insert tools
 - **Accuracy $\pm 2\%$ of the scale value** (in the direction of actuation)
Can be used for right-hand and left-hand threads by turning the insert tool
 - Safe:
 - Haptic (close-gap release)
 - Audible (“click” sound)
 - With calibration certificate and serial number
 - Safe and fast adjustment of the desired torque value by turning the handle
 - Secure storage in safe box with inspection window
 - DIN EN ISO 6789-2:2017
 - Made in Germany
 - Output:
 - Dimensions: 625 mm
 - For manual operation
 - Torque range min-max: 60 – 320 Nm
 - Accuracy: 2 %
 - Scale Graduation (Nm): 2 Nm
 - Effective torque wrench length min.-max. l1 mm: 592.00 – 573.80 Nm
 - Actuating force min.-max. kg: 10.3 – 56.8 kg
 - Inside micrometre of the adjusting tool l2: 38.5 mm
 - Head Thickness a: 23 mm
 - Head Width b: 30 mm
 - **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required
- DAkkS calibration certificate** for the professional user, especially for:
- Aviation industry
 - Automobile industry
 - New-energy, wind turbines, offshore wind farms
 - Petrochemical industry (oil/gas)
- Documented traceability guarantees complete verifiability

Order Number

6293-1 CT CAL