

# Product data sheet

## 995 S 6/6

EAN-No. 4000896264780



6-pieces · T40 · T45 · T50 · 1/2, ·



### Application:

Screw connections on commercial vehicles and passenger cars with inside TORX® profile  
e.g. on chassis, brake systems

- 3/4" (20 mm) drive allows transmission of high separation forces
- 995S6-T50LG operation of the screw connection on the steering knuckle for the brake discs / wheel bearings on the **FORD** Transit model year 2006 →
- Optionally available adapter 1003S-1 for 3/4" (20 mm) drive
- Choice of drive 1/2" (12.5 mm) or 24 mm
- With borehole for locking pin or safety spring and groove for O-ring
- Safety-Insert-System, 2-component soft foam insert.  
Insert also suitable for HAZET Assistent
- Surface: phosphatized, oiled
- Made in Germany
- Drive: 1/2,
- Output:
- For impact operation
- Number of tools: 6

Order Number

995 S 6/6



995S6 · · 1/2,  
T40



995S6 · · 1/2,  
T45



995S6 · · 1/2,  
T50





995S6 · · 1/2,  
T40

# Product data sheet


## 995 S 6/6

EAN-No. 4000896264780



995S6 •   1/2,  
T45



995S6 •   1/2,  
T50