## Product data sheet 4904-10 EAN-No. 4000896236213



## 64 - 115 mm ·



- Compact HAZET design enables spring replacement with remarkable time savings
- Universal application on almost all passenger cars
- Tensioning jaw · span width 64 115 mm
- Anti-rotation device for lower tensioning jaws integrated in the base component reduces the outer diameter to 32 mm
- Pendulum 6-point head for uniform distribution of power
- Integrated anti-rotation device for upper clamping plates
- One-sided counterholder for the spindle by hexagon on top, e.g. with combination wrench HAZET 600N-13
- Removal and installation of springs with small coil spacing, e.g. for the MINI Cooper S (third generation) · VW Passat (B8)
- Span 120 mm
- Loading up to 31,000 N work safely on electric and hybrid vehicles
- GS mark for tested safety tested with at least four-fold safety against breakage
- 17° angular movement of the tensioning jaws ensures removal of C-shaped (bent) springs, e.g. AUDI A4 (B9) · VW Golf 7
- Internal and external guidance the clamping plates prevents the spring from sliding out
- All clamping plates included, reusable, replaceable plastic protective pads
- Tested on vehicles of the following manufacturers:

 $\textbf{AUDI} \cdot \textbf{BMW} \cdot \textbf{CITROËN} \cdot \textbf{FIAT} \cdot \textbf{FORD} \cdot \textbf{HYUNDAI} \cdot \textbf{KIA} \cdot \textbf{MAZDA} \cdot \textbf{MERCEDES-BENZ} \cdot \textbf{MINI} \cdot \textbf{OPEL} \cdot \textbf{PEUGEOT} \cdot \textbf{RENAULT} \cdot \textbf{SEAT} \cdot \textbf{SKODA} \cdot \textbf{TOYOTA} \cdot \textbf{VW}$ 

## Highlights:

- · Easy handling for just one user
- Eliminates time-consuming work associated with most spring removal:
  - Removal of axle parts unnecessary
  - Axle alignment no longer necessary
  - Removal and installation possible in just a few minutes on each side
- Made in Germany
- Diameter (min-max): 64 115 mm

Order Number 4904-10