Product data sheet 5123-3 CT EAN-No. 4000896218998



Length: 628 mm · Torque range min-max: 60 – 320 Nm · Accuracy: 3 % · 2 1/2

Color Manuel Color



- SYSTEM 5000-3 CT -
- Accuracy ± 3% of the scale value (in direction of actuation for right-hand tightening) (5107-3CT ± 4% accuracy of scale value)
- For left-hand tightening, use our torque wrenches with insert tool
- Safe:
 - Haptic (close-gap release)
- Audible ("click" sound)
- Designed for rough workshop use
- Wide range of applications for controlled screw tightening in tyre service, bicycle, passenger car and commercial vehicle applications as well as various applications in trade and industry
- · Optimised sealing ring to protect against debris
- Ratchet repair set for customer-oriented self-assembly enables decades of use
- Handle with better grip for easier power transmission
- Adjustment aid with detent points for optimised operator guidance ensures safe and fast adjustment of the desired torque value by turning the handle
- · Safe locking of the setting values by latching function on the rotary assembly
- · Rotary assembly in triangular form prevents uncontrolled rolling
- · Lock symbols indicate the respective locking status
- · Can be attached to the cable loop through openings on the locking rotary assembly
- Easy-to-read, high-contrast scale
- Permanent readability due to laser marking on the scale bush
- Integrated shift lever

5121-3CT - 5123-3CT: shift lever with idle function - reduces risk of injury and malfunction

- · With calibration certificate and serial number
- Delivery in sturdy Hexa plastic box
- DIN EN ISO 6789-2:2017, DIN 3120, ISO 1174-1
- Made in Germany
- Output: 125 1/2
- Dimensions: 628 mm
- Net weight: 1.5 kg
- For manual operation
- Torque range min-max: 60-320 Nm
- Accuracy: 3 %
- Scale Graduation (Nm): 2 Nm
- Actuating force min.-max. kg: 11.3-62.2 kg

Product data sheet 5123-3 CT EAN-No. 4000896218998



- Number of teeth: 32 (Opening angle 11.25°)
- Head Thickness a: 19.6 mm
- Head Width b: 44 mm
- No more turning back: Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

Order Number

5123-3 CT