Product data sheet 903 S Lg 6-21 EAN-No. 4000896262960



Size 21 mm ⋅ 125 1/2, ⋅ 📵



Application:

Actuation of stiff wheel bolts with option for using a $^{3}/_{4}"$ (20 mm) impact wrench Especially for vans and light trucks, such as e.g. **FIAT** Ducato, **MERCEDES-BENZ** Sprinter

- Operation via impact adapter e.g. HAZET 1003S-1 or nut-drivers s 24 mm enables high force transmission thanks to optimal ³/₄" (20 mm) drive
- · Plastic sleeve yellow
- Hexagon on the socket enables adaptation to 3/4" (20 mm) drive
- · Double protection: easy-to-rotate external plastic sleeve (replaceable) to protect the rims when screwing wheel bolts
- Colour-coded plastic sleeve for quickly finding the correct wrench size
- Plus: internal plastic insert to protect the surface of wheel bolts
- Long design
- With borehole for locking pin or safety spring and groove for O-ring
- DIN 3129, ISO 2725-2
- Made in Germany
- Drive: 129 1/2,
- Output: 🕲
- Wrench size: 21 mm
- Dimensions / length: 87 mm
- Diameter d1 (output side): 31.2 mm
- Diameter d2 (drive side): 27 mm
- For impact operation

Order Number 903 S Lg 6-21