Product data sheet 6295-1 CT EAN-No. 4000896026203



Length: 962 mm · Torque range min-max: 200 – 500 Nm · Accuracy: 2 % · □



- Plug connection for holding insert tools
- Accuracy ± 2 % of the scale value (in the direction of actuation)
 Can be used for right-hand and left-hand threads by turning the insert tool
- · Safe:
 - Haptic (close-gap release)
- Audible ("click" sound)
- With calibration certificate and serial number
- Safe and fast adjustment of the desired torque value by turning the handle
- Secure storage in safe box with inspection window
- 2-component handle for improved feel
- · Simplified locking for adjusting the torque value
- Viewing window for visual checking of the locking
- Knob for additionally locking the set value
- 4 coloured coding rings (red, yellow, green, black) for markings in the case of personalisation or special workflows
- DIN EN ISO 6789-2:2017
- Made in Germany
- Output: 🖽
- Dimensions / length: 962 mm
- Net weight: 4.32 kg
- For manual operation
- Torque range min-max: 200 500 Nm
- Accuracy: 2 %
- Scale Graduation (Nm): 2.5 Nm
- Effective torque wrench length min.-max. I1 mm: 937.20 925.20 Nm
- Actuating force min.-max. kg: 21.8 55.1 kg
- Inside micrometre of the adjusting tool I2: 44 mm
- Head Width b: 35.5 mm
- No more turning back: Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

SYSTEM 6200-1 CT insert torque wrench \cdot 2 – 500 Nm \cdot with insert square \cdot accuracy \pm 2 / 4 %

Order Number 6295-1 CT