

Product data sheet

916 HP Lg

EAN-No. 4000896233076



614 mm · $\frac{1}{2}$ · Ausziehbar



Application:

Small operating angle (4°) enables use in the tightest of spaces, e.g. Engine, machine construction, agricultural vehicles and devices, renewable energy (solar, wind turbines)

- A lot more power for ratchets with the same dimensions
- Continuously adjustable from 414 to 614 mm (without pre-fixed detent points)
- Easy fixation with knurled clamping nut
- Twist protected handle ensures optimum force transmission without slipping
- Locking function of the lever prevents unwanted switching
- Increased service life thanks to the use of state-of-the-art lubricants in the ratchet mechanism
- Strict production tolerances prevent dirt from getting in
- HAZET internal quality standards guarantee loading capacity far beyond the standard requirements
- High-quality, easy to clean, corrosion-resistant
- Integrated suspension option in the handle
- VPA tested, static torque according to DIN 3122: 1000 Nm
- **Extra long design**
- Number of teeth: 90 (Opening angle 4°)
- Locking ball
- HAZET 2-component handle
- Surface: chrome-plated
- ≈ DIN 3122, ≈ ISO 3315
- Made in Germany
- Output: $\frac{1}{2}$
- Dimensions: 614 mm
- Length l1: 414 mm
- For manual operation
- **HiPer – The Original**
- Developed and produced "Made in Germany"
- Static AND dynamic – double precision in perfection
- High permanent load for durability
- Ergonomic **shift lever**

Handle

HAZET 2-component handle

Order Number

916 HP Lg