Product data sheet 6281-2 CT EAN-No. 4000896183326



Length: 125.4 mm · Torque range min-max: 5 - 13 Nm · Accuracy: 4 % · □x□ ·



Application:

Regulation of the control valve at the gas tank of **VW** Up! and Caddy model years 2012 → (adjustment is necessary after installation or removal)

- Extra short construction for areas with restricted access
- Plug connection for holding insert tools
- Accuracy ± 4 % of the scale value (in the direction of actuation)
 Can be used for right-hand and left-hand threads by turning the insert tool
- · Safe:
 - Haptic (close-gap release)
 - Audible ("click" sound)
- With calibration certificate and serial number
- Safe and fast adjustment of the desired torque value by turning the handle
- Surface: hard chrome plated
- DIN EN ISO 6789-2:2017
- Made in Germany
- Output: 9x12
- Dimensions: 125.4 mmNet weight: 0.23 kg
- · For manual operation
- Torque range min-max: 5 13 Nm
- Accuracy: 4 %
- Scale Graduation (Nm): 0.2 Nm
- Effective torque wrench length min.-max. I1 mm: 116.50 112.50 Nm
- Actuating force min.-max. kg: 4.4 11.8 kg
- Inside micrometre of the adjusting tool I2: 17.5 mm
- Head Thickness a: 17 mm
- Head Width b: 22 mm
- No more turning back: Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

Order Number 6281-2 CT