Product data sheet 6295-1 CT CAL EAN-No. 4000896193110



With DAkkS calibration certificate · Length: 962 mm · Torque range min-max: 200 – 500 Nm · Accuracy: 2 % · •••• •



- Torque wrench with DAkkS calibration certificate
- Plug connection for holding insert tools
- Accuracy ± 2 % of the scale value (in the direction of actuation)
 Can be used for right-hand and left-hand threads by turning the insert tool
- Safe
 - Haptic (close-gap release)
 - Audible ("click" sound)
- · With calibration certificate and serial number
- Safe and fast adjustment of the desired torque value by turning the handle
- · Secure storage in safe box with inspection window
- 2-component handle for improved feel
- Simplified locking for adjusting the torque value
- Viewing window for visual checking of the locking
- Knob for additionally locking the set value
- 4 coloured coding rings (red, yellow, green, black) for markings in the case of personalisation or special workflows
- DIN EN ISO 6789-2:2017
- Made in Germany
- Output: 🖽
- Dimensions: 962 mm
- For manual operation
- Torque range min-max: 200 500 Nm
- Accuracy: 2 %
- Scale Graduation (Nm): 2.5 Nm
- Effective torque wrench length min.-max. I1 mm: 937.20 925.20 Nm
- Actuating force min.-max. kg: 21.8 55.1 kg
- Inside micrometre of the adjusting tool I2: 44 mm
- Head Width b: 35.5 mm
- No more turning back: Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

DAkkS calibration certificate for the professional user, especially for:

- · Aviation industry
- · Automobile industry
- New-energy, wind turbines, offshore wind farms
- Petrochemical industry (oil/gas)

Documented traceability guarantees complete verifiability

Product data sheet 6295-1 CT CAL EAN-No. 4000896193110



Order Number 6295-1 CT CAL