

Product data sheet

615-S 10 x 12

EAN-No. 4000896203505



Size 10 x 12 mm • ● •



Application:

Safe operation of control bar screw connection (loosening, adjusting, tightening) when removing or installing the pressurized can with position sensor for boost pressure plate on the turbocharger

- Working on built-in components
- Bent double box-end wrench (12-point), slotted on sides (s 10 mm)
- Can be used in combination with HAZET socket **2561-10**
- For 2.0 l common rail engines (4-cylinder diesel engines)
- **VW** Golf model year 2009 → · Golf Plus model year 2009 → · Eos model year 2006 → · Jetta model year 2006 → · Passat model year 2006 → · Passat CC model year 2009 → · Beetle model year 2011 → · Scirocco model year 2009 → · Tiguan model year 2008 → · Transporter model year 2010 →
- **AUDI** A3 model year 2004 → · TT model year 2008 → 2014
- **SEAT** Altea model year 2006 → · León model year 2006 → 2012 · Toledo model year 2006 → 2009
- **ŠKODA** Octavia model year 2006 → 2013 · Superb model year 2009 → 2015 · Yeti model year 2009 →
- **Motor Code diesel:**
CAAA · CAAB · CAAD · CAAE · CCHB · CAAC · CFFD · CBDC · CLCA · CLJA · CBAA · CFFA · CJAA · CBAB · CTHC · CFFB · CFJA · CBBB · CBAC · CFGA · CRBC · CRLB · CBBA · CBDA · CBDA · CEGA · BKP · BMA · BMR · BKD · AZ
- Made in Germany
- Output: ●
- Wrench size: 10 x 12 mm
- Dimensions: 147 mm

Order Number

615-S 10 x 12