

Product data sheet

5121-2 CLT CAL

EAN-No. 4000896243242



With DAkkS calibration certificate · Length: 435 mm · Torque range min-max: 20 – 120 Nm · Accuracy: 4 % ·

125 1/2



- Click-Lens-Type with large display in the inspection window guarantees security for the user
- Torque wrench **with DAkkS calibration certificate**
- **Accuracy $\pm 4\%$ of the scale value** (in direction of actuation for right-hand tightening)
For left-hand tightening, use our torque wrenches with insert tool
- Safe:
 - Haptic (close-gap release)
 - Audible (“click” sound)
- Reversible ratchet
- Safe and fast adjustment of the desired torque value by turning the handle
- Knob for additionally locking the set value
- Three large digits for an easy-to-read torque setting
- With calibration certificate and serial number
- Secure storage in safe box with inspection window
- Surface: hard chrome plated
- DIN EN ISO 6789-2:2017, DIN 3120, ISO 1174-1
- Made in Germany
- Output: 125 1/2
- Dimensions: 435 mm
- For manual operation
- Torque range min-max: 20 – 120 Nm
- Accuracy: 4 %
- Scale Graduation (Nm): 1 Nm
- Actuating force min.-max. kg: 5.9 – 37.0 kg
- Number of teeth: 32 (Opening angle 11.25°)
- Head Thickness a: 19.6 mm
- Head Width b: 44 mm
- **Service-friendly** (do-it-yourself repair sets for ratchets)
- No risk of losing the square like there is with the wrench
- **Hard chrome-plated** steel tube - **slim**, but very sturdy and wear-resistant
- Integrated shift lever with free-running function on 125 1/2 model **reducing the risk of injury and malfunction**
- Ergonomically shaped handle with collar **reduces the risk of slipping-off and injury**
- Safety locking of the handle – no risk of injury!
- Safe and exact adjustment of the desired release torque.
Optimal and easy reading of the torque value
- Large convex display (replaceable) optimises the readability

Product data sheet

5121-2 CLT CAL

EAN-No. 4000896243242



- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

DAkkS calibration certificate for the professional user, especially for:

- Aviation industry
- Automobile industry
- New-energy, wind turbines, offshore wind farms
- Petrochemical industry (oil/gas)

Documented traceability guarantees complete verifiability Torque tools in industry

Order Number

5121-2 CLT CAL