## Product data sheet 5121-2 CLT EAN-No. 4000896104215



Length: 435 mm · Torque range min-max: 20 - 120 Nm · Accuracy: 4 % · 2 1/2 ·



- · Click-Lens-Type with large display in the inspection window guarantees security for the user
- Accuracy ± 4 % of the scale value (in direction of actuation for right-hand tightening)
   For left-hand tightening, use our torque wrenches with insert tool
- Safe
  - Haptic (close-gap release)
  - Audible ("click" sound)
- Reversible ratchet
- Safe and fast adjustment of the desired torque value by turning the handle
- Knob for additionally locking the set value
- Three large digits for an easy-to-read torque setting
- · With calibration certificate and serial number
- · Secure storage in safe box with inspection window
- Surface: hard chrome plated
- DIN EN ISO 6789-2:2017, DIN 3120, ISO 1174-1
- Made in Germany
- Output: 125 1/2
- Dimensions: 435 mmNet weight: 1.17 kg
- For manual operation
- Torque range min-max: 20 120 Nm
- Accuracy: 4 %
- Scale Graduation (Nm): 1 Nm
- Actuating force min.-max. kg: 5.9 37.0 kg
- Number of teeth: 32 (Opening angle 11.25°)
- Head Thickness a: 19.6 mm
- Head Width b: 44 mm
- Service-friendly (do-it-yourself repair sets for ratchets)
- No risk of losing the square like there is with the wrench
- Hard chrome-plated steel tube slim, but very sturdy and wear-resistant
- Integrated shift lever with free-running function on 

  "" model reducing the risk of injury and malfunction
- Ergonomically shaped handle with collar reduces the risk of slipping-off and injury
- Safety locking of the handle no risk of injury!
- Safe and exact adjustment of the desired release torque.
   Optimal and easy reading of the torque value
- · Large convex display (replaceable) optimises the readability
- No more turning back: Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

## Product data sheet 5121-2 CLT EAN-No. 4000896104215



Drehmomentwerkzeuge in der Industrie

Order Number 5121-2 CLT