

Product data sheet

6280-1 CT CAL

EAN-No. 4000896193073



Length: 181 mm · Torque range min-max: 2 – 10 Nm · Accuracy: 2 % ·  · With DAkkS calibration certificate



- Torque wrench **with DAkkS calibration certificate**
 - Plug connection for holding insert tools
 - **Accuracy $\pm 2\%$ of the scale value** (in the direction of actuation)
Can be used for right-hand and left-hand threads by turning the insert tool
 - Safe:
 - Haptic (close-gap release)
 - Audible ("click" sound)
 - With calibration certificate and serial number
 - Especially slim design thanks to spring-loaded puller sleeve for locking the setting values
 - Safe and fast adjustment of the desired torque value by turning the handle
 - DIN EN ISO 6789-2:2017
 - Made in Germany
 - Output: 
 - Dimensions: 181 mm
 - For manual operation
 - Torque range min-max: 2 – 10 Nm
 - Accuracy: 2 %
 - Scale Graduation (Nm): 0.2 Nm
 - Effective torque wrench length min.-max. l1 mm: 160.40 – 154.40 Nm
 - Actuating force min.-max. kg: 1.3 – 6.6 kg
 - Inside micrometre of the adjusting tool l2: 19.5 mm
 - Head Thickness a: 17 mm
 - Head Width b: 22 mm
 - **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required
- DAkkS calibration certificate** for the professional user, especially for:
- Aviation industry
 - Automobile industry
 - New-energy, wind turbines, offshore wind farms
 - Petrochemical industry (oil/gas)
- Documented traceability guarantees complete verifiability

Order Number

6280-1 CT CAL