Product data sheet

4937-92 EAN-No. 4000896**201952**



114 mm · 20 3/4



- Pin wrench **MAN** TGX, TGA, TGS all models, model year 2000 →
- For e.g. front axle V9-82L-01 (disc brake with ABS) and **MERCEDES-BENZ** Atego rear axle as well as **MAN** · **MERCEDES-BENZ** · **VAN HOOL** and **NEOPLAN** buses
- Inside Ø: 100.5 mm
- Inside Ø (pin-pin): 92.5 mm
- Outside Ø: 114 mm
- 6 internal pins · 7 mm wide
- \square Drive $^3\!\!/_4$ " (20 mm) as well as outside hexagon s 46 mm
- Use possible with 3/4" (20 mm) impact wrench (9013MG · 9013M) and torque wrench (6145-1CT · 6150-1CT)
- · Precise fit
- Precise pin geometry for ideal tool operation in pin nuts
- Solid design: High (shape) stability even with high loosening or tightening torques
- Screw connection tightening torque 750 800 Nm (please observe manufacturer's instructions)
- For MAN Lkw: E 2000 (ÖAF) F 2000 M 2000 L M 2000 M

 $\textbf{MAN} \; \mathsf{TGA} \cdot \mathsf{TGM} \cdot \mathsf{TGS} \cdot \mathsf{TGX}$

- MAN buses: Lion's City · Lion's Classic · Lion's Coach · Lion's Regio · Lion's Star as well as older constructions (models) · chassis
- **NEOPLAN** Cityliner · Starliner · Tourliner · Trendliner
- TEMSA Diamond · VISEON high-decker
- Surface: burnished
- Made in Germany
- Drive: 20 3/4
- Dimensions: 84 mm
- Diameter: 114 mm
- For manual operation

Order Number 4937-92