## Product data sheet 6292-1 CT EAN-No. 4000896026135



Length: 511 mm · Torque range min-max: 40 - 200 Nm · Accuracy: 2 % · 🔤 ·



- Plug connection for holding insert tools
- Accuracy ± 2 % of the scale value (in the direction of actuation)
  Can be used for right-hand and left-hand threads by turning the insert tool
- Safe
- Haptic (close-gap release)
- Audible ("click" sound)
- · With calibration certificate and serial number
- Safe and fast adjustment of the desired torque value by turning the handle
- Secure storage in safe box with inspection window
- DIN EN ISO 6789-2:2017
- Made in Germany
- Output: 🖽
- Dimensions: 511 mmNet weight: 1.05 kg
- For manual operation
- Torque range min-max: 40 200 Nm
- Accuracy: 2 %
- Scale Graduation (Nm): 1 Nm
- Effective torque wrench length min.-max. I1 mm: 478.00 455.44 Nm
- Actuating force min.-max. kg: 8.5 44.8 kg
- Inside micrometre of the adjusting tool I2: 38.5 mm
- Head Thickness a: 23 mm
- Head Width b: 30 mm
- No more turning back: Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

Order Number 6292-1 CT