Product data sheet 6001-1.4/3 EAN-No. 4000896190980



3-pieces · Torque range min-max: 0.4 – 1.4 Nm · Accuracy: 15 % · ⊕ ¼



- For all fittings with low torque e.g. disc brakes on bicycles
- For all screw connections with low torque e.g. valve cores on tyre pressure control systems
- For tightening torques from 0.4 1.4 Nm
- Torque release clearly palpable and audible when torque setting is reached by ratcheting
- Release without torque function
- Fast and precise setting of torque values with offset screwdriver (HAZET 2100-06, included in delivery)
- Insert tool holder for bits with magnet for all bits with 🗣 drive or HAZET adapter 2304N for connecting to 🖾 ¼ HAZET 850 sockets
- Accuracy in a manner consistent with EN ISO 6789
- Contents:

Handle with insert tool holder for bits 2239-7, offset screwdriver 2100-06

- Plastic handle
- Made in Germany
- Output: [©]

 √
- Net weight: 0.2 kg
- For manual operation
- Torque range min-max: 0.4 1.4 Nm
- Accuracy: 15 %

Torque screwdriver 6001 \cdot for bits \cdot 0.4 – 5.4 Nm \cdot accuracy \pm 6 / 15 %

• Number of tools: 3

Handle	Plastic handle
Order Number	6001-1.4/3