Product data sheet 5107-3 CT EAN-No. 4000896218875



Length: 234 mm · Torque range min-max: 1 - 9 Nm · Accuracy: 4 % · ■ ¼ ·



- · User-friendly reversible ratchet
- · For working on motorcycles, bicycles and tyre pressure control systems
- SYSTEM 5000-3 CT -
- Accuracy ± 3% of the scale value (in direction of actuation for right-hand tightening) (5107-3CT ± 4% accuracy of scale value)
- For left-hand tightening, use our torque wrenches with insert tool
- · Safe:
 - Haptic (close-gap release)
 - Audible ("click" sound)
- Designed for rough workshop use
- Wide range of applications for controlled screw tightening in tyre service, bicycle, passenger car and commercial vehicle applications as well as various applications in trade and industry
- Optimised sealing ring to protect against debris
- Ratchet repair set for customer-oriented self-assembly enables decades of use
- Handle with better grip for easier power transmission
- Adjustment aid with detent points for optimised operator guidance ensures safe and fast adjustment of the desired torque value by turning
 the handle
- Safe locking of the setting values by latching function on the rotary assembly
- Rotary assembly in triangular form prevents uncontrolled rolling
- · Lock symbols indicate the respective locking status
- Can be attached to the cable loop through openings on the locking rotary assembly
- Easy-to-read, high-contrast scale
- Permanent readability due to laser marking on the scale bush
- Integrated shift lever

5121-3CT - 5123-3CT: shift lever with idle function - reduces risk of injury and malfunction

- With calibration certificate and serial number
- Delivery in sturdy Hexa plastic box
- DIN EN ISO 6789-2:2017, DIN 3120, ISO 1174-1
- Made in Germany
- Output: 63 1/4"
- Dimensions: 234 mm
- Net weight: 0.42 kg
- For manual operation
- Torque range min-max: 1 9 Nm
- Accuracy: 4 %

Product data sheet 5107-3 CT EAN-No. 4000896218875



• Scale Graduation (Nm): 0.1 Nm

• Actuating force min.-max. kg: 0.6 - 5.5 kg

• Number of teeth: 20 (Opening angle 18°)

• Head Thickness a: 10.2 mm

• Head Width b: 24 mm

• No more turning back: Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required

Drehmomentwerkzeuge in der Industrie

Order Number 5107-3 CT